

IDI BMC B90 (Glass Content 8%)

Thermoset, Unspecified

IDI Composites International

Message:

PRODUCT SERIES: B90 SERIES BMC

PRODUCT DESCRIPTION: CORROSION RESISTANT GRADE

These composites are typically unsaturated polyester or epoxy vinyl ester materials formulated to meet the strict performance requirements of pumps, pipe flanges & underground applications that are impacted by corrosive environments.

General Information			
Filler / Reinforcement	Glass Fiber,8.0% Filler by Weight		
Features	Good Corrosion Resistance		
Uses	Pump Parts		
Forms	BMC - Bulk Molding Compound		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.50 to 2.00	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.0 to 0.20	%	ASTM D955
Water Absorption (23°C, 24 hr)	0.10 to 0.30	%	ASTM D570
Hardness	Nominal Value	Unit	Test Method
Barcol Hardness	30 to 60		ASTM D2583
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	27.6	MPa	ASTM D638
Flexural Strength	68.9	MPa	ASTM D790
Compressive Strength	96.5	MPa	ASTM D695
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	370	J/m	ASTM D256
Unnotched Izod Impact	530	J/m	ASTM D4812
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	> 204	°C	ASTM D648
Flammability	Nominal Value	Unit	Test Method
Burning Rate	7.9	mm/min	ASTM D635

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

