

# Durez® 14000

Phenolic

SBHPP

## Message:

Durez® 14000 is a finely powdered, thermosetting resin of the two-step type. It is formulated to give a good balance of properties to friction materials and is recommended for use in the manufacture of dry mix brake linings and disc pads.

| General Information                 |               |      |                 |
|-------------------------------------|---------------|------|-----------------|
| Uses                                | Lining        |      |                 |
| Appearance                          | Colorless     |      |                 |
| Forms                               | Powder        |      |                 |
| Thermal                             | Nominal Value | Unit | Test Method     |
| Melting Temperature <sup>1</sup>    | 80.0          | °C   | Internal method |
| Additional Information              | Nominal Value | Unit | Test Method     |
| Inclined Plate Flow - 0.5 g (125°C) | 3.00          | cm   | Internal method |
| Screen Mesh - 200 mesh              | 0.90          | %    | Internal method |
| Uncured Properties                  | Nominal Value | Unit | Test Method     |
| Curing Time (165°C)                 | 8.3E-3        | hr   | Internal method |
| NOTE                                |               |      |                 |
| 1.                                  | Shrink        |      |                 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT