# Sylvin 8036-65 Clear Yellow 4172

### Polyvinyl Chloride

Sylvin Technologies Incorporated

#### Message:

Sylvin 8036-65 Clear Yellow 4172 Is A Vinyl Compound Formulated For Extrusion Applications. This Compound Contains A Polymeric Plasticizer For Low Migration And Increased Chemical Resistance.

General Information			
Additive	Plasticizer		
Features	Plasticized		
	Good chemical resistance		
	General		
	Mobility Low to None		
Uses	Industrial application		
	General		
Appearance	Yellow		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.23	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness			ASTM D2240
Shaw A	65		ASTM D2240
Shaw A, 10 seconds	65		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	12.1	MPa	ASTM D638
Tensile Elongation (Break)	430	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	43.8	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	163 - 174	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

