

Diakon® CLH374

Polymethyl Methacrylate Acrylic

Lucite International Inc.

Message:

Diakon® CLH374 is a Polymethyl Methacrylate Acrylic material. It is available in Europe for injection molding.

Important attributes of Diakon® CLH374 are:

Flame Rated

Good Mold Release

General Information			
UL YellowCard	E108947-218755		
Features	Good Flow		
	Good Mold Release		
Forms	Granules		
Processing Method	Injection Molding		
Impact	Nominal Value	Unit	Test Method
Instrumented Dart Impact	0.600	J	ASTM D3763
Thermal	Nominal Value	Unit	Test Method
CLTE - Flow	7.1E-5	cm/cm/°C	ASTM D696
Flammability	Nominal Value		Test Method
Flame Rating	HB		UL 94
Optical	Nominal Value	Unit	Test Method
Refractive Index	1.490		ASTM D542
Transmittance	92.0	%	ASTM D1003
Haze	0.40	%	ASTM D1003

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT