

VINIKA® CC70DN

Flexible Polyvinyl Chloride

Mitsubishi Chemical Performance Polymers, Inc.

Message:

VINIKA® CC70DN is a Flexible Polyvinyl Chloride material. It is available in Asia Pacific for extrusion.
Typical application of VINIKA® CC70DN: Automotive

General Information			
Uses	Automotive Applications		
	Automotive Interior Parts		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	1.24	g/cm ³	JIS K7112
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (10 sec)	71		JIS K6253
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress			JIS K6723
Break	18.0	MPa	
100% Strain	6.50	MPa	
Tensile Strain (Break)	400	%	JIS K6723

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

