

PIVINEL™ VHR-1

Polyvinyl Chloride
HELLENIC CABLES S.A.

Message:

Description: PVC based compounds for cables in hydrocarbon resistance power cables
Specifications: VDE 207 TYPE TM3-TM5, YM2-ST2 (HYDROCARBON RESISTANT)
Packaging: In PE bags of 25 kg or in big bags of approximately 1000 kg
Types of cables where it can be used: NYSLYCYO, NYSLYO.

General Information		
Features	Hydrocarbon Resistant	
Uses	Wire & Cable Applications	
Processing Method	Extrusion	
Physical	Nominal Value	Unit
Specific Gravity	1.36	g/cm ³
Extrusion	Nominal Value	Unit
Cylinder Zone 1 Temp.	145	°C
Cylinder Zone 2 Temp.	150	°C
Cylinder Zone 3 Temp.	150	°C
Cylinder Zone 4 Temp.	155	°C
Cylinder Zone 5 Temp.	155	°C
Cylinder Zone 6 Temp.	160	°C
Cylinder Zone 7 Temp.	160	°C
Head Temperature	160	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT