

Jam PE 52518

High Density Polyethylene
Jam Petrochemical Company

Message:

Jam PE 52518 is a High Density Polyethylene product. It can be processed by injection molding and is available in Africa & Middle East. Typical application: Household Applications.
Characteristics include:
Copolymer
High Flow

General Information			
Features	Copolymer		
	High Flow		
	Narrow Molecular Weight Distribution		
Uses	Household Goods		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.950 to 0.954	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	16 to 20	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus (Compression Molded)	> 1350	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	> 25	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	> 122	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT