

# Eltex® HD5240GA-B

High Density Polyethylene Copolymer

INEOS Olefins & Polymers Europe

## Message:

Eltex® HD5240GA-B is a high density polyethylene copolymer grade with a narrow molecular weight distribution, specially developed for injection of caps and closures applications requiring good environmental stress-cracking resistance. Thanks to high purity and excellent organoleptic properties, this grade is particularly intended for the packaging in direct contact with beverages.

### Typical applications

Caps and closures for the packaging of juices, functionalized beverages and slightly carbonated or pressurized beverages

### Benefits and Features

Easy processing

Good environmental stress cracking resistance

High impact strength

Low warpage

Grade containing slip agent ensuring easy application and opening. Exposure to direct sunlight has to be avoided as the slip agent is light sensitive and its degradation can give off-taste to the beverage.

Excellent, quality controlled organoleptic properties. In order to preserve the excellent organoleptic properties, it is important not to exceed a melt temperature of 250°C during processing.

General Information			
Additive	slip agent		
Features	Ultra-high impact resistance		
	High purity		
	Low warpage		
	High ESCR (Stress Cracking Resistance)		
	Copolymer		
	smoothness		
	Workability, good		
	Good sensory characteristics		
Uses	Shield		
	Shell		
RoHS Compliance	Contact manufacturer		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Density	0.950	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	4.0	g/10 min	ISO 1133
Environmental Stress-Cracking Resistance	13.0	hr	ASTM D1693
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	1100	MPa	ISO 527-2/1B
Tensile Stress (Yield)	25.0	MPa	ISO 527-2/1B

Impact	Nominal Value	Unit	Test Method
Charpy Unnotched Impact Strength (23°C)	5.5	kJ/m <sup>2</sup>	ISO 179
Additional Information			

The value listed as Density ASTM D1183, was tested in accordance with ASTM D1872. The value listed as Eniro. Stress Crack Res. ASTM D1693, was tested in accordance with INEOS test methods. Organoleptic Properties, INEOS methods: OK

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

### Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

