

Neopor® F 5300

Expanded Polystyrene

BASF Corporation

Message:

Application

Neopor® is used to manufacture silver-gray colored foams that have considerably better thermal insulation capacity than conventional EPS products.

For the production of expanded foams having fire characteristics in conformity with:

DIN 4102-B1 (flame retardant)

EN ISO 13501-1-E

Product description

Expandable polystyrene (EPS) containing uniformly distributed flame-retardant. Blowing agent: pentane.

Additional information pertaining to the fire behavior can be found in the technical information sheet titled "Fire -protec tion behavior of foams made of Styropor®".

Neopor® F 5300 : For blocks and shapes with wall thicknesses over 8mm

General Information		
UL YellowCard	E41871-101746622	
Additive	Blowing Agent 3	
	Flame Retardant	
Features	Flame Retardant	
Uses	Foam	
	Insulation	
Agency Ratings	DIN 4102/B1	
	EC 1907/2006 (REACH)	
RoHS Compliance	RoHS Compliant	
Appearance	Grey	
Forms	Granules	
Physical	Nominal Value	Unit
Apparent Density		
-- ¹	0.02	g/cm ³
--	0.02 to 0.03	g/cm ³
Moisture Content	< 0.50	%
Sieve Analysis		
< 800.0 µm	< 2.0	%
0.800 to 1.50 mm	> 95	%
> 1.50 mm	< 3.0	%
Aging - intermediate	0.4 to 2.0	day
Bead Size	0.900 to 1.40	mm
NOTE		

-
- | | |
|----|--|
| 1. | Obtainable in a single pre-foaming operation |
|----|--|

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

