

Caltex PP M710H

Polypropylene Impact Copolymer

GS Caltex

Message:

Caltex PP M710H is a Polypropylene Impact Copolymer (PP Impact Copolymer) material. It is available in Asia Pacific. Primary attribute of Caltex PP M710H: Impact Resistant.
Typical applications include:
Bottles
Sheet

General Information			
Features	Good Stretchability		
	High Impact Resistance		
Uses	Blow Molding Applications		
	Bottles		
	Sheet		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.900	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	0.33	g/10 min	ASTM D1238
Molding Shrinkage			ASTM D955
Flow	1.5 to 1.8	%	
Across Flow	1.5 to 1.8	%	
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	80		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	25.5	MPa	ASTM D638
Tensile Elongation			ASTM D638
Yield	10	%	
Break	> 500	%	
Flexural Modulus	1030	MPa	ASTM D790A
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	> 490	J/m	ASTM D256
Gardner Impact	> 24.5	J	ASTM D3029
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	110	°C	ASTM D648
Vicat Softening Temperature	146	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

