Shandong PA66 ZRPA66

Polyamide 66

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PA66 ZRPA66 is a Polyamide 66 (Nylon 66) material. It is available in Asia Pacific. Important attributes of Shandong PA66 ZRPA66 are: Flame Rated Good Toughness Heat Resistant Impact Resistant Wear Resistant Wear Resistant Typical applications include: Engineering/Industrial Parts Appliances

General Information			
Features	Good Toughness		
	Good Wear Resistance		
	High Heat Resistance		
	High Impact Resistance		
	Lubricated		
Uses	Appliance Components		
	Bearings		
	Machine/Mechanical Parts		
Mechanical	Nominal Value	Unit	
Tensile Stress (Yield)	65.0	MPa	
Tensile Strain (Break)	20	%	
Flexural Stress	70.0	MPa	
Impact	Nominal Value	Unit	
Notched Izod Impact Strength	30	kJ/m²	
Unnotched Izod Impact Strength	No Break		
Thermal	Nominal Value	Unit	
Heat Deflection Temperature (0.45 MPa,			
Unannealed)	220	°C	
Flammability	Nominal Value		Test Method
Flame Rating	НВ		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

