

INTEX® 2720

Emulsion Styrene Butadiene Rubber

Versalis S.p.A.

Message:

Intex 2720 is an aqueous anionic dispersion of a styrene-butadiene copolymer with high solid content obtained by emulsion polymerisation using fatty acid soap as emulsifier. It does not contain any antioxidant.

Key Features

Intex 2720, vulcanised, shows excellent mechanical properties.

Main Applications

Intex 2720 is mainly used for high stiffness moulded foam obtained by both Dunlop and Talalay process.

General Information			
Features	Copolymer		
	Foamable		
	High Stiffness		
	Vulcanizable		
Uses	Foam		
Appearance	White		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Bound Styrene	37.0	%	Internal Method
pH	10.3		ISO 976
Solids Content	66.0	wt%	ISO 124
Brookfield Viscosity ¹	1.00	Pa·s	ISO 1652
NOTE			
1.	60 rpm		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

