Geon™ Vinyl Flexible XV3845

Flexible Polyvinyl Chloride

PolyOne Corporation

Message:

Geon™Vinyl Flexible XV3845 is a flexible polyvinyl chloride product. It can be processed by blow molding and is available in North America, Africa and the Middle East, Latin America, Europe or Asia Pacific. Geon™The application areas of Vinyl Flexible XV3845 include food contact applications, bottles and medical/health care. The main characteristics are: accessible food.

General Information				
Features	Compliance of Food Exposure			
Uses	Bottle			
	Medical devices			
Agency Ratings	FDA Food Exposure, Not Rated			
	FDA not rated			
Appearance	Clear/transparent			
Forms	Particle			
Processing Method	Blow molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.30	g/cm³	ASTM D792	
Hardness	Nominal Value	Unit	Test Method	
Durometer Hardness (Shore D, 10 sec)	60		ASTM D2240	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength ¹ (Break)	26.6	MPa	ASTM D638	
Tensile Elongation ² (Break)	200	%	ASTM D638	
Thermal	Nominal Value	Unit	Test Method	
Brittleness Temperature	-60.0	°C	ASTM D746	
Additional Information				

注释:本化合物配方中所用的全部成分均在美国食品及药物管理局《联邦法规法典》第21章中列出.唯一的限制是,增塑剂"仅用于高含水量食物". 本说明仅为食品及药物管理局清单关于该产品内容的概述.

由用户负责确保此化合物适用于其预期用途.注释:填充温度必须低于150°F注释:不能用于包装牛奶.

NOTE	
1.	Type 4, 510mm/min
2.	Type 4, 510mm/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

