

# Luxus PP 16292

Polypropylene Copolymer

Luxus Limited

Message:

Luxus PP 16292 is a Polypropylene Copolymer (PP Copolymer) material filled with 20% mineral. It is available in Europe.

Important attributes of Luxus PP 16292 are:

Eco-Friendly/Green

Copolymer

General Information			
Filler / Reinforcement	Mineral,20% Filler by Weight		
Recycled Content	Yes		
Features	Copolymer		
Appearance	Black		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	18 to 22	g/10 min	ISO 1133
Molding Shrinkage	0.70 to 1.4	%	
Ash Content (650°C)	15000	mm	
Drying Temperature	80	°C	
Drying Time	2.0	hr	
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	20.0 to 24.0	MPa	ISO 527-2
Tensile Strain (Break)	15	%	ISO 527-2
Flexural Modulus	1240 to 1650	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength	4.5 to 8.0	kJ/m²	ISO 180
Multi-Axial Instrumented Impact Peak Force	800 to 950	N	ISO 527

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT