

# Hifax TRS 372P

Polyolefin

LyondellBasell Industries

## Message:

Hifax TRS 372P is an elastomeric thermoplastic polyolefin designed for injection moulding. It combines very good processability with medium stiffness/excellent impact properties. The product contains UV stabilisation designed for outdoor application. Typical applications are spoiler. The grade is available in custom colour, pellet form.

General Information			
Additive	UV Stabilizer		
Features	Good Impact Resistance		
	Good Processability		
	Good Stiffness		
Uses	Automotive Applications		
	Automotive Exterior Parts		
Appearance	Colors Available		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm <sup>3</sup>	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	23	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield, 23°C)	13.0	MPa	ISO 527-2/50
Flexural Modulus - Secant <sup>1</sup> (23°C)	550	MPa	ISO 178
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	60.0	°C	ISO 75-2/B
NOTE			
1.	2.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

