

Lusin® Protect G 11

Unspecified

Chem-Trend L.P.

Message:

Grease-like Anticorrosion Agent

Benefits

Stable, transparent film

Resistant to low and high temperatures

Repels moisture

Ensures temporary protection against corrosion

Description

Lusin® Protect G11 is a grease-like anticorrosion agent based on highly refined hydrocarbon oils and special additives for temporary protection of all kinds of metal surfaces.

The elastic, polymolecular film penetrates into tiny cracks and corners, and spreads under humid spots.

Lusin® Protect G11 is free from silicone, resistant to low temperatures, and does not drip. Besides aerosol and ready-to-use version the product is also available as concentrate for special applications.

Typical Properties

Anticorrosion behaviour, DIN 50017 : No corrosion after 10 h

Salt spray test, 5% NaCl solution, at 35°C (95°F), DIN 50021 : No corrosion after 5 h

Application

Lusin® Protect G 11 is mainly used to protect moulds and dies dedicated for processing thermoplastic resins against corrosion.

General Information		
Appearance	Clear/transparent	
Forms	Liquid	
Thermal	Nominal Value	Unit
Service Temperature		°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

