

# BorSafe™ HE3495-LS-H

High Density Polyethylene

Borealis AG

## Message:

BorSafe HE3495-LS-H is a bimodal polyethylene compound produced by the advanced Borstar technology.

The compound contains a stabilisation package that has been specifically designed to fully protect the polyethylene against thermal and UV degradation.

Furthermore, it has a pigment system that gives a bright colored stripe, even when extruded as a thin layer on a black pipe.

General Information			
Additive	Heat Stabilizer		
	UV Stabilizer		
Features	Bimodal Molecular Weight Distribution		
	Heat Stabilized		
	Recyclable Material		
Uses	Piping		
Appearance	Blue		
Processing Method	Coextrusion		
	Pipe Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.951	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	0.25	g/10 min	ISO 1133

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT