Kumho EPS GN20

Expanded Polystyrene

Korea Kumho Petrochemical Co., Ltd.

Message:

Features: General

Applications: Packing materials, Box,

General Information				
Features	General Purpose			
Uses	General Purpose			
	Packaging			

Physical	Nominal Value	Unit	Test Method
Density	0.0200	g/cm³	Internal Method
Water Absorption	0.300	g/100 cm²	Internal Method
Molded Density	17.0 to 20.0	kg/m³	Internal Method
Compressive Strength	0.100	MPa	Internal Method
Bead Size	600.0 to 900.0	μm	Internal Method
Blowing Agent	5.0	%	Internal Method
Flexural Demolition Load	27	N	Internal Method
Optimum Expansion Multiple	70.0		Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

