

# Fixmaster 4 Minute Putty

Epoxy; Epoxide

Loctite®

## Message:

Fixmaster 4 Minute Putty is an epoxy; Epoxy resin products contain steel fillers. It is available in North America. Fixmaster 4 Minute Putty's application areas include industrial applications, food contact applications and repair materials.

| General Information          |                           |      |             |
|------------------------------|---------------------------|------|-------------|
| Filler / Reinforcement       | Steel filler              |      |             |
| Features                     | Machinable                |      |             |
|                              | Fast curing               |      |             |
| Uses                         | Industrial application    |      |             |
|                              | Metal repair materials    |      |             |
| Agency Ratings               | USDA Unspecified Approval |      |             |
| Appearance                   | Grey                      |      |             |
| Forms                        | Particle                  |      |             |
| Hardness                     | Nominal Value             |      | Test Method |
| Durometer Hardness (Shore D) | 83                        |      | ASTM D2240  |
| Mechanical                   | Nominal Value             | Unit | Test Method |
| Tensile Strength (Yield)     | 10.3                      | MPa  | ASTM D638   |
| Compressive Strength         | 41.4                      | MPa  | ASTM D695   |
| Thermal                      | Nominal Value             | Unit | Test Method |
| Continuous Use Temperature   | 107                       | °C   | ASTM D794   |
| Thermoset                    | Nominal Value             | Unit |             |
| Pot Life (25°C)              | 3.0 - 4.0                 | min  |             |
| Demold Time (25°C)           | 10                        | min  |             |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT