

# Spherisil P 21-08690

Polyethylene

SILON s.ro

## Message:

Absorbent Polymer preparation specially developed for the Spherisil® P process for Pipes.

Applications: Spherisil® P process for Pipes intended to be used for sanitary and heating applications.

Combinations: SPHERISIL P 21-08690 must be used together with a suitable grade of HDPE and a compatible Silane blend for the Spherisil P process like Silmix 59D2. For further questions please contact our technical department.

General Information			
Features	Porous		
Uses	Piping		
Agency Ratings	EU 2002/72/EC FDA 21 CFR 177.1520 (a), (b) and (c)		
Appearance	White		
Forms	Powder		
Physical	Nominal Value	Unit	Test Method
Density	0.955	g/cm <sup>3</sup>	ASTM D1505
Apparent Density	0.25	g/cm <sup>3</sup>	ASTM D1895
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	3.8	g/10 min	ASTM D1238
Additional Information	Nominal Value	Unit	Test Method
Volatiles	< 0.10	%	ASTM D3030

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

