

Guang Sung PVC NBR-PVC 60

Polyvinyl Chloride
Guang Sung Plastics (GSPL)

Message:

Guang Sung PVC NBR-PVC 60 is a Polyvinyl Chloride product. It can be processed by extrusion and is available in Asia Pacific. Applications of Guang Sung PVC NBR-PVC 60 include automotive, construction applications, engineering/industrial parts, hose/tubing and wire & cable. Primary characteristic: rohs compliant.

General Information			
Features	High Elasticity		
Uses	Acoustic Barrier		
	Automotive Interior Trim		
	Automotive Under the Hood		
	Cable Jacketing		
	Gaskets		
	Hose		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Extrusion		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A)	59		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain)	2.60	MPa	ASTM D412
Tensile Strength (Yield)	9.43	MPa	ASTM D412
Tensile Elongation (Break)	750	%	ASTM D412
Thermal	Nominal Value	Unit	Test Method
Heat Loss	0.80	%	JIS K6723

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT