

Braskem PP HP 427J

Polypropylene Homopolymer

Braskem

Message:

HP 427J is a low fluidity homopolymer with good processability. The product is suitable for both as monolayer and coextruded structures. It does not contain any slip or anti-blocking agents.

Applications:

BOPP films with greater retention in treatment over the metallized layer.

Processing:

Bioriented Film (BOPP)

General Information			
Features	Good Processability Homopolymer Low Flow		
Uses	Film		
Agency Ratings	FDA 21 CFR 177.1520		
Processing Method	Bi-axially Oriented Film		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.905	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	3.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, Injection Molded)	33.0	MPa	ASTM D638
Tensile Elongation (Yield, Injection Molded)	9.0	%	ASTM D638
Flexural Modulus - 1% Secant (Injection Molded)	1400	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C, Injection Molded)	35	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT