

tefabloc® TO 222

Thermoplastic Elastomer

Mitsubishi Chemical Performance Polymers, Inc.

Message:

The tefabloc® engineering plastics make use of the elastomeric properties of styrenic bloc co-polymer (SBS) and of hydrogenated styrenic bloc co-polymers (SEBS). The specific structure of tefabloc® combines the physical properties of a vulcanised rubber with the advantages of a thermoplastic. Their specific compositions give these TPEs a very good resistance to oxidation, detergents, acids and ozone and a very good weatherability. tefabloc® performs surprisingly well at low temperatures by keeping its mechanical and flexibility properties, where many other plastics become hard and brittle.

The product range of tefabloc® is one of the widest found, with very low hardness starting from 5 Shore A, the flexible grades from 40 to 80 Shore A and the semi-rigids up to 60 Shore D. We offer colour-matched compounds as well natural grades that can be easily coloured with masterbatch.

General Information		
Additive	UV Stabilizer	
Features	Acid Resistant	
	Base Resistant	
	Detergent Resistant	
	Food Contact Acceptable	
	Good Chemical Resistance	
	Good Thermal Stability	
	Good UV Resistance	
	Good Weather Resistance	
	Oxidation Resistant	
	Ozone Resistant	
Appearance	Translucent	
Processing Method	Injection Molding	
Hardness	Nominal Value	Test Method
	30	
Shore Hardness (Shore A)	80	ISO 868
Thermal	Nominal Value	Unit
Service Temperature	-40 to 80	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

