

CEPLA CEW-671

Polypropylene

CEPLA Co., LTD

Message:

CEPLA CEW-671 is a Polypropylene material filled with filler. It is available in Asia Pacific, Europe, or Latin America.

Important attributes of CEPLA CEW-671 are:

Good Weather Resistance

Impact Resistant

Typical application of CEPLA CEW-671: Automotive

General Information			
Filler / Reinforcement	Filler		
Features	Good Weather Resistance		
	High Impact Resistance		
Uses	Automotive Applications		
	Automotive Exterior Parts		

Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.980	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	20	g/10 min	ASTM D1238

Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	18.6	MPa	ASTM D638
Flexural Modulus	1180	MPa	ASTM D790

Impact	Nominal Value	Unit	Test Method
Unnotched Izod Impact			ASTM D256
-30°C	25	J/m	
23°C	160	J/m	

Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature	100	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT