Spartech Polycom X02474

Polypropylene Homopolymer

Spartech Polycom

Message:

Spartech Polycom X02474 is a polypropylene homopolymer (PP Homopoly) product containing a filler of 20% barium sulfate. It is available in North America. The main characteristics are: good processing performance.

General Information			
Filler / Reinforcement	Barium sulfate, 20% filler by weigh	t	
Features	Workability, good		
Appearance	Black		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.14	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16			
kg)	10	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	31.0	MPa	ASTM D638
Tensile Elongation			ASTM D638
Yield	7.0	%	ASTM D638
Fracture	50	%	ASTM D638
Flexural Modulus - Secant	1520	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	43	J/m	ASTM D256
Dart Drop Impact (23°C)	3.39	J	ASTM D3029

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

