Weifang Kingdom CM35-1

Chlorinated Polyethylene Elastomer

Weifang Kingdom Plastic Co., Ltd

Message:

FEATURES: It can be used not only as halide rubber solely but also mixed with CR, CSM, NBR, SBR and NR at any proportion. APPLICATION: Manufacture kinds of flame resistant cable & wire sleeve, rubber pipe, flame resistant conveyor belt, rubber parts, rubber sealing plate, insulating layer of cable & wire and roof waterproof coil, etc.

| General Information | | | | | |
|----------------------------------|-----------------------------|------|-------------|--|--|
| Features | Flame Retardant | | | | |
| | Good Chemical Resistance | | | | |
| | Good Weather Resistance | | | | |
| | High Molecular Weight | | | | |
| | Low Temperature Flexibility | | | | |
| | Low to No Taste | | | | |
| | Oil Resistant | | | | |
| | | | | | |
| Uses | Automotive Applications | | | | |
| | Blending | | | | |
| | Cable Jacketing | | | | |
| | Conveyors | | | | |
| | Hose | | | | |
| | Insulation | | | | |
| | Marine Applications | | | | |
| | Mining Applications | | | | |
| | Piping | | | | |
| | Seals | | | | |
| | Wire Jacketing | | | | |
| | | | | | |
| Appearance | White | | | | |
| Forms | Powder | | | | |
| Physical | Nominal Value | Unit | Test Method | | |
| Mooney Viscosity (ML 1+4, 121°C) | 45 to 55 | MU | GB/T 1232 | | |
| Chlorine Content | 34.0 to 36.0 | wt% | GB/T 9872 | | |
| Hardness | Nominal Value | Unit | Test Method | | |
| Shore Hardness | < 56 | | GB/T 531 | | |
| Elastomers | Nominal Value | Unit | Test Method | | |
| Tensile Strength | > 8.50 | MPa | GB/T 528 | | |
| Tensile Elongation (Break) | > 700 | % | GB/T 528 | | |
| Thermal | Nominal Value | Unit | Test Method | | |
| Heat of Fusion | < 1.00 | J/g | DSC | | |

| Volatiles | < 0.50 | % | GB/T 2914 |
|-----------|--------|---|-----------|
| | | | |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

