

# Chemraz 517

Perfluoroelastomer  
Greene, Tweed & Co.

Message:

Chemraz 517 is a Perfluoroelastomer product. It is available in North America. Applications of Chemraz 517 include engineering/industrial parts, housings and sealing applications. Primary characteristic: low temperature resistant.

General Information			
Features	Low Temperature Resistant		
Uses	Housings		
	Pump Parts		
	Seals		
Appearance	White		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.21	g/cm <sup>3</sup>	ASTM D297
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	80		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress			ASTM D1414
50% Strain	3.72	MPa	
100% Strain	7.24	MPa	
Tensile Strength (Break)	11.0	MPa	ASTM D1414
Tensile Elongation (Break)	170	%	ASTM D1414
Compression Set <sup>1</sup> (204°C, 70 hr)	25	%	ASTM D395
Thermal	Nominal Value	Unit	
Service Temperature	-30 to 220	°C	
NOTE			
1.	25% Deflection		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519  
Phone: +86 13424755533  
Email: sales@su-jiao.com  
No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT