

Moplen HP2674

Polypropylene Homopolymer

LyondellBasell Industries

Message:

Moplen HP2674 is suitable for extrusion applications. It has a very high melt flow rate, a very narrow molecular weight distribution and is in pelletized form. Moplen HP2674 is suitable for the production of meltblown nonwovens and is also used for compounding applications. For regulatory information please refer to Moplen HP2674 Product Stewardship Bulletin (PSB)

General Information			
Features	High Flow		
	Homopolymer		
	Narrow Molecular Weight Distribution		
Processing Method	Compounding Extrusion		
	Meltblown Nonwovens		
Physical	Nominal Value	Unit	Test Method

Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	800	g/10 min	ISO 1133
---	-----	----------	----------

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

