

Hax™ HFC 087/2

Polyolefin

Fainplast Compounds S.r.l

Message:

Hax™ HFC 087/2 is a Polyolefin product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Wire & Cable.

Characteristics include:

Flame Retardant

Halogen Free

General Information			
Additive	Flame Retardant		
Features	Flame Retardant		
	Halogen Free		
	Low Smoke Emission		
Uses	Wire & Cable Applications		
Physical	Nominal Value	Unit	Test Method
Density	1.88 to 1.92	g/cm ³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D, 15 sec)	34 to 40		ISO 868
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity (20°C)	> 1.0E+12	ohms · cm	IEC 60093
Flammability	Nominal Value	Unit	Test Method
Oxygen Index	35 to 45	%	ISO 4589-2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

