

# Huaфон T25SYK

Polyamide 66

Huaфон Group Co., Ltd.

## Message:

T25SYK is semi-dull and middle-low viscosity resin, with good spinnability and dyeing properties.

### Typical Applications

T25SYK is mainly used in POY filament, as well as fine denier textile yarn.

General Information	
Filler / Reinforcement	Titanium Dioxide,0.30% Filler by Weight
Features	Medium-low Viscosity
Uses	Filaments Yarn

Physical	Nominal Value	Unit	Test Method
Density	1.14	g/cm <sup>3</sup>	ISO 1183
Apparent Density	0.70	g/cm <sup>3</sup>	Internal Method
Particle Size	2.20 to 2.80	g/100 pellets	Internal Method
Relative Viscosity	2.42 to 2.50		Internal Method
Water Content	< 5000	mg/kg	Internal Method
Thermal	Nominal Value	Unit	Test Method
Peak Melting Temperature <sup>1</sup>	257	°C	ASTM D3418
NOTE			

1. 10°C/min

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

