TECHLEN M2302HK

Polypropylene

DAEHA Co., LTD

Message:

TECHLEN M2302HK is a Polypropylene material filled with glass fiber. It is available in Asia Pacific. Primary attribute of TECHLEN M2302HK: High Stiffness. Typical application of TECHLEN M2302HK: Automotive

General Information				
Filler / Reinforcement	Glass Fiber			
Features	High Stiffness			
Uses	Automotive Application	Automotive Applications		
	Automotive Under the I	Hood		
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.11	g/cm³	ASTM D792	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	100		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength	68.6	MPa	ASTM D638	
Flexural Modulus	3330	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Unnotched Izod Impact (23°C)	180	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (0.4 MPa, Unannealed)	45 140	°C	ASTM D648	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

