

# Hostacom BB 1161 G

Polypropylene Copolymer

LyondellBasell Industries

## Message:

Hostacom BB 1161 G is a high melt flow rate, 12% mineral filled, UV stabilised polypropylene copolymer. The product is designed for automotive interior applications. This grade is available in custom color, pellet form.

General Information			
Filler / Reinforcement	Mineral,12% Filler by Weight		
Additive	UV Stabilizer		
Features	Copolymer		
	Good Processability		
	Good UV Resistance		
	High Flow		
	Non-Toxic		
Uses	Automotive Applications		
	Automotive Interior Parts		
Appearance	Colors Available		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.990	g/cm <sup>3</sup>	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	28	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus	1900	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	5.0	kJ/m <sup>2</sup>	ISO 180/1A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT