

MTEGRITY™ LLDPE LL800

Linear Low Density Polyethylene

M. Holland Company

Message:

MTEGRITY™ LLDPE LL800 is a Linear Low Density Polyethylene product. It can be processed by injection molding and is available in North America. Applications of MTEGRITY™ LLDPE LL800 include caps/lids/closures, containers, engineering/industrial parts and household applications. Characteristics include:

- Fast Molding Cycle
- High Gloss
- Impact Resistant
- Low to No Odor/Taste
- Warp Resistant

General Information			
Features	Fast Molding Cycle		
	High Gloss		
	Low Temperature Impact Resistance		
	Low to No Odor		
	Low Warpage		
Uses	Containers		
	Household Goods		
	Lids		
	Thin-walled Parts		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.925	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	50	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	14.5	MPa	ASTM D638
Tensile Elongation (Break)	8.0	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

