

Eltex® B6921/40N2010

High Density Polyethylene

INEOS Olefins & Polymers Europe

Message:

Coloured stripes are often co-extruded on black pipe to enable the end use to be identified. The appropriate stripe products are available for use with the PE 80 series pipe compounds as listed below.

Applications:

For identification of Gas/Water applications

Benefits and Features:

Coloured stripe compounds for use with PE 80 compounds

General Information			
Uses	Piping		
RoHS Compliance	Contact Manufacturer		
Appearance	Light Blue		
Processing Method	Coextrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.948	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/5.0 kg)	0.45	g/10 min	ISO 1133
Color ¹	5012		
NOTE			
1.	RAL n°		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

