# TRILAC® ABS-MP1000

### Acrylonitrile Butadiene Styrene

Polymer Technology and Services, LLC

#### Message:

TRILAC® ABS-MP1000 is an Acrylonitrile Butadiene Styrene (ABS) product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Primary characteristic: flame rated.

General Information				
Features	Platable			
Forms	Pellets			
Processing Method	Injection Molding			
Physical	Nominal Value	Unit	Test Method	
Specific Gravity	1.04	g/cm³	ASTM D792	
Melt Mass-Flow Rate (MFR) (220°C/10.0 kg)	23	g/10 min	ASTM D1238	
Hardness	Nominal Value	Unit	Test Method	
Rockwell Hardness (R-Scale)	103		ASTM D785	
Mechanical	Nominal Value	Unit	Test Method	
Tensile Strength (Yield)	44.8	MPa	ASTM D638	
Tensile Elongation (Break)	25	%	ASTM D638	
Flexural Modulus	2250	MPa	ASTM D790	
Flexural Strength (Yield)	73.1	MPa	ASTM D790	
Impact	Nominal Value	Unit	Test Method	
Notched Izod Impact (3.17 mm)	290	J/m	ASTM D256	
Thermal	Nominal Value	Unit	Test Method	
Deflection Temperature Under Load (1.8 MPa, Unannealed)	89.0	°C	ASTM D648	
Flammability	Nominal Value		Test Method	
Flame Rating			UL 94	
1.59 mm	НВ			
3.17 mm	НВ			
Injection	Nominal Value	Unit		
Drying Temperature	87.8 to 93.3	°C		
Drying Time	2.0 to 24	hr		
Rear Temperature	193	°C		
Middle Temperature	216	°C		
Front Temperature	232	°C		
Processing (Melt) Temp	218 to 260	°C		
Mold Temperature	48.9 to 65.6	°C		
Injection Pressure	68.9 to 82.7	МРа		
Injection Rate	Slow-Moderate			

Back Pressure	0.689	MPa
Screw Speed	50 to 60	rpm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

