ARBOBLEND® V4

Biodegradable Polymers

TECNARO GmbH

Message:

Thermoplastics from renewable resources for plastics processing

Our granules ARBOFORM [®] , ARBOBLEND [®] and ARBOFILL [®] can be processed with injection moulding, extrusion, calendering, blow molding, deep drawing or pressing into moulded parts, half-finished product, sheets, films oder profiles.

ARBOBLEND© granules are 100% biodegradable and show comparable material properties as classic plastics with high impact strength(e.g. ABS). Depending on the application, ARBOBLEND© contains different biopolymers like e.g. Polyhydroxialkanoate, Polyester, Ingeo TM, Lignin, Starch, Cellulose, organic additives, natural resins or waxes and natural reinforcing fibers.

General Information			
Features	Biodegradable		
	Renewable Resource Content		
Uses	Bottles		
	Furniture		
	Sheet		
Forms	Pellets		
Processing Method	Blow Molding		
	Calendering		
	Extrusion		
	Injection Molding		
	Press Molding		
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2160	MPa	ISO 527-2
Tensile Stress			ISO 527-2
Yield	39.2	MPa	
Break	24.3	MPa	
Tensile Strain			ISO 527-2
Yield	2.4	%	
Break	> 10	%	
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	No Break		ISO 179

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

