

# Ravalene CR LS 5241

Low Density Polyethylene

Ravago Group

Message:

IQ compound LDPE natural for film + slip

General Information			
Additive	Slip		
Recycled Content	Yes		
Features	Slip		
Uses	Film		
Appearance	Natural Color		
Processing Method	Film Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.925	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.3	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	10.0	MPa	ISO 527-2
Tensile Strain			ISO 527-2
Yield	25	%	
Break	500	%	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT