

UNITEM® Rg-30

Polyether Imide
Nytel Plastics, Ltd.

Message:

UNITEM Polyetherimide (PEI) is an amorphous thermoplastic that is manufactured from SABIC Innovative Plastics' ULTEM resin. UNITEM PEI is extremely rigid, dimensionally stable, and able to withstand continuous operating temperatures of 340°F. Because it offers superior resistance to autoclave sanitizing and is FDA/USDA compliant, UNITEM PEI is routinely specified for reusable machined components used in the medical and pharmaceutical industries. This material also offers electronic and semiconductor designers unmatched dielectric properties that are maintained over a wide frequency range. Unfilled UNITEM PEI is dark amber in color and semi-transparent. For applications that require improved stiffness, glass fiber filled grades with filler levels of 10%-40% are available. Nytel Plastics' UNITEM PEI stock shapes are UL V-0 rated and available in a full range of heavy gauge rod, plate and tubular bar sizes.

PRODUCT ATTRIBUTES

- 340°F continuous use temperature
- Semi-transparent with light amber color
- Excellent strength and rigidity, even at elevated temperatures
- Low moisture absorption
- Superior electrical properties
- Rated UL V-0
- Easily machined and fabricated
- FDA, USDA compliant
- Glass fiber filled grades for improved strength and stiffness

INDUSTRIES

- Medical and pharmaceutical
- Aircraft and aerospace
- Fluid handling
- Electrical and electronics manufacturing
- Microwave communications

APPLICATIONS

- Sight glasses
- Manifolds
- Electrical insulators
- Electrical component housings
- Aircraft instrumentation

General Information	
Filler / Reinforcement	Glass Fiber,30% Filler by Weight
Features	Amorphous
	Autoclave Sterilizable
	Good Dimensional Stability
	Good Electrical Properties
	High Rigidity
	High Strength
	Low Moisture Absorption
	Machinable
Uses	Aerospace Applications
	Aircraft Applications
	Aircraft Interiors
	Electrical Parts

Electrical/Electronic Applications

Eyeglasses

Fluid Handling

Medical/Healthcare Applications

Pipe Seals

Appearance	Clear Amber
Forms	Preformed Parts
	Rod

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.51	g/cm ³	ASTM D792
Water Absorption			ASTM D570
24 hr	0.16	%	
Saturation	0.90	%	

Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness			ASTM D785
M-Scale	114		
R-Scale	127		

Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	5520	MPa	ASTM D638
Tensile Strength (Yield)	117	MPa	ASTM D638
Tensile Elongation (Break)	13	%	ASTM D638
Flexural Modulus	5860	MPa	ASTM D790
Flexural Strength	186	MPa	ASTM D790
Compressive Strength	212	MPa	ASTM D695

Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	85	J/m	ASTM D256

Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	210	°C	ASTM D648
Continuous Use Temperature	171	°C	UL 746
Vicat Softening Temperature	228	°C	ASTM D3418
CLTE - Flow	2.0E-5	cm/cm/°C	ASTM D696

Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	> 1.0E+16	ohms · cm	ASTM D257
Dielectric Strength ¹	30	kV/mm	ASTM D149
Dielectric Constant			ASTM D150
60 Hz	3.70		
1 MHz	3.70		
Dissipation Factor (60 Hz)	1.5E-3		ASTM D150

Flammability	Nominal Value	Unit	Test Method
--------------	---------------	------	-------------

Flame Rating (3.18 mm)	V-0	UL 94
NOTE		

1.	Method A (Short-Time)
----	-----------------------

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT