

ICORENE® N2106

Low Density Polyethylene

ICO Polymers EMEA, A Division of A. Schulman

Message:

ICORENE® N2106 is an easy flowing low density polyethylene grade with medium stiffness and good toughness.

General Information			
Features	Good Flow		
	Good Stiffness		
	Good Toughness		
Uses	Masterbatch		
Forms	Powder		
Processing Method	Compounding Extrusion		
	Scatter Coating		
Physical	Nominal Value	Unit	Test Method
Density	0.924	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	22	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	44		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	200	MPa	ASTM D638
Tensile Elongation (Break)	120	%	ASTM D638
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	89.0	°C	ASTM D1525
Peak Melting Temperature	108	°C	ASTM D3418

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT