

Vinnolit® S 3160

Polyvinyl Chloride
Vinnolit GmbH & Co. KG

Message:

Vinnolit S 3160 is a free-flowing suspension polymer with excellent fusion properties. It is recommended for sheet, profile and film manufacturing. A distinguishing feature of Vinnolit S 3160 is its extremely low fish-eye count.

General Information			
Uses	Film		
	Profiles		
	Sheet		
Agency Ratings		EC 1907/2006 (REACH)	
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.56	g/cm³	ISO 60
K-Value	60.0		ISO 1628-2
Viscosity Number (Reduced Viscosity)	89.0	ml/g	ISO 1628
Particle Size Distribution			ISO 4610
-- 1	< 1.0	%	
-- 2	> 97	%	
Volatile Matter	< 0.30	%	ISO 1269
NOTE			
1.	retained on 0.250 mm screen		
2.	retained on 0.063 mm screen		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT