NuSil MED-2014

Silicone

NuSil Technology

Message:

NuSil Technology's restricted materials may be considered for use in short-term implant applications, 29 days or less, or for external applications. "Dispersion" is a term used to describe a silicone elastomer system that is suspended or dispersed in a solvent carrier. It is a complex solution that contains silicone polymers of various molecular weights and reinforcing fillers. The substituent groups comprising the polymer back bone structure may consist of the following: Polydimethylsiloxane, Dimethyl Diphenyl copolymer, and Fluoro homo polymer or copolymer. Silicone dispersions typically have low viscosities, which is beneficial for applications wherein a thin film coating is needed, and they can easily be used in dipping and spraying processes. NuSil uses a variety of solvents to disperse silicones, such as xylene, tert butyl acetate, heptane, hexane, acetone and naphtha. Comments: ONE PART, IN XYLENE

General Information			
Filler / Reinforcement	Filler		
Features	Low Viscosity		
Uses	Coating Applications		
	Medical/Healthcare Applications		
Agency Ratings	USP Class VI		
Forms	Dispersion		
Processing Method	Dip Coating		
	Spraying		
Mechanical	Nominal Value	Unit	
Tensile Strength (200% Strain)	1.03	MPa	
Additional Information	Nominal Value	Unit	
Cure System	Platinum		
Uncured Properties	Nominal Value	Unit	
Density	1.10	g/cm³	
Viscosity	3.5	Pa·s	
Curing Time ¹	2.0	hr	
Cured Properties	Nominal Value	Unit	
Shore Hardness (Shore A)	35		

Shore Hardness (Shore A)	35		
Tensile Strength	12.4	MPa	
Tensile Elongation at Break	800	%	
Tear Strength	32.4	kN/m	
NOTE			
1.	1h/50°C + 1h/150°C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

