

Trovicel® 19/24 mm

Flexible Polyvinyl Chloride

Röchling Engineering Plastics SE & Co. KG

Message:

- Product characteristics
- Low weight
- Excellent rigidity
- UV and weather resistance
- Typical field of application
- Visual communication
- Building industry

General Information			
Features	Good UV Resistance		
	Good Weather Resistance		
	High Rigidity		
Uses	Building Materials		
	Construction Applications		
Physical	Nominal Value	Unit	Test Method
Density	0.550	g/cm³	ISO 1183
Water Absorption (Equilibrium, 23°C, 50% RH)	< 0.20	%	ISO 62
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore D)	80		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	700	MPa	ISO 527-2
Thermal	Nominal Value	Unit	Test Method
CLTE - Flow	6.0E-5 to 8.0E-5	cm/cm/°C	DIN 53752

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT