Hifax EKC 287P

Polypropylene Impact Copolymer LyondellBasell Industries

Message:

"Hifax" EKC 287P is a medium flow, 10% mineral filled, highly UV stabilized, high impact polypropylene copolymer with excellent scratch resistants suitable for injection molding. The grade has been specifically designed for molding unpainted large complex parts that require a high impact strength as well as a good stiffness by keeping a very good surface quality under heavy use.

This	arade	is	available	in	custom	color.	pellet form.

General Information						
Filler / Reinforcement	Mineral,10% Filler by Weight					
Additive	UV Stabilizer					
Features	Good Abrasion Resistance					
	Good Color Stability					
	Good Moldability					
	Good Stiffness					
	Good UV Resistance					
	Good Weather Resistance					
	High Impact Resistance					
	Impact Copolymer					
	Medium Flow					
	Pleasing Surface Appearance					
	Scratch Resistant					
Uses	Automotive Applications					
	Automotive Exterior Parts					
Appearance	Colors Available					
Forms	Pellets					
Processing Method	Injection Molding					
Physical	Nominal Value	Unit	Test Method			
Density	0.970	g/cm³	ISO 1183			
Melt Mass-Flow Rate (MFR) (230°C/2.16						
kg)	14	g/10 min	ISO 1133			
Mechanical	Nominal Value	Unit	Test Method			
Tensile Stress (Yield)	16.0	MPa	ISO 527-2/50			
Tensile Strain (Break)	100	%	ISO 527-2/50			
Flexural Modulus - Secant	1300	MPa	ISO 178			
Impact	Nominal Value	Unit	Test Method			
Notched Izod Impact Strength			ISO 180/1A			
-30°C	6.0	kJ/m²				

-20°C	8.0	kJ/m²	
23°C	No Break		
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	125	°C	ISO 306/A50

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

