Duron PA 6,6 10GF-IML

Polyamide 66

ProPolymers Inc.

Message:

Duron PA 6,6 10GF-HSL is an impact modified, nucleated 10% glass reinforced nylon 6,6 that offers a superior combination of mechanical, electrical, and thermal properties. It is lubricated which improves mold release and surface finish. Duron PA provides outstanding processability and good chemical resistance

General Information					
Filler / Reinforcement	Glass Fiber,10% Filler by Weight				
Additive	Impact Modifier				
	Lubricant				
	Nucleating Agent				
Features	Good Chemical Resistance				
	Good Mold Release				
	Good Processability				
	Good Surface Finish				
	Impact Modified				
	Lubricated				
	Nucleated				
Forms	Pellets				
Physical	Nominal Value	Unit	Test Method		
Specific Gravity	1.16	g/cm³	ASTM D792		
Molding Shrinkage			ASTM D955		
Flow : 3.18 mm	0.60 to 0.80	%			
Across Flow: 3.18 mm	0.70 to 0.80	%			
Water Absorption (24 hr)	0.70	%	ASTM D570		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	119		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield, 23°C)	90.0	МРа	ASTM D638		
Tensile Elongation (Break, 23°C)	10	%	ASTM D638		
Flexural Modulus (23°C)	3960	МРа	ASTM D790		
Flexural Strength (23°C)	155	МРа	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact (23°C)	110	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		
Deflection Temperature Under Load			ASTM D648		
0.45 MPa, Unannealed	244	°C			

1.8 MPa, Unannealed	210	°C	
Melting Temperature	249	°C	
CLTE - Flow	3.5E-5	cm/cm/°C	ASTM D696

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

