

WALL-LITE 80-10

Polyurethane
DIC Corporation

Message:

PANDEX, WALL-LITE series are single-pack and twin-pack polyurethane resins developed for waterproofing of rooftops and walls and adhesion of rubber chips. The series characteristically excel in workability and hardening effects.

| General Information | | |
|------------------------------|----------------------------|-------------|
| Features | Good Processability | |
| | Low to No Water Absorption | |
| Uses | Adhesives | |
| | Sealants | |
| Appearance | White | |
| Forms | Paste | |
| Processing Method | Spraying | |
| Hardness | Nominal Value | Test Method |
| Durometer Hardness (Shore A) | 60 | JIS A6021 |
| Elastomers | Nominal Value | Unit |
| Tensile Strength (Yield) | 4.00 | MPa |
| Tensile Elongation (Break) | 500 | % |
| Tear Strength | 23.0 | kN/m |
| Additional Information | Nominal Value | Unit |
| Hardening Time (25°C) | 18.0 | hr |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT