

INEOS PP 240-NA02

Polypropylene Random Copolymer

INEOS Olefins & Polymers Europe

Message:

240-NA02 is a random copolymer for blow moulding with good transparency and contact clarity, very good gloss and surface finish and high heat distortion temperature.

Applications

240-NA02 is recommended for:

Household

Industrial chemicals

Cosmetics

The product is also suited for injection stretch blow moulding.

General Information	
Features	Good Surface Finish
	High Clarity
	High Gloss
	High Heat Resistance
	Random Copolymer
Uses	Cosmetics
	Household Goods
	Industrial Containers
RoHS Compliance	Contact Manufacturer
Forms	Pellets
Processing Method	Blown Film
	Injection Blow Molding

Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	1.5	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	900	MPa	ISO 527-2
Tensile Stress (Yield)	24.0	MPa	ISO 527-2/50
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength (23°C)	20	kJ/m²	ISO 179/1eA

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

