

Hostacom BB 1161 F M 2678

Polypropylene Copolymer
LyondellBasell Industries

Message:

Hostacom BB1161 F M is a high melt flow, mineral filled, UV resistant polypropylene copolymer. The product ehxibits excellent processability and high stiffness. It has been designed for automotive interior applications.
The grade is available in custom colours and in pellet form.

General Information			
Filler / Reinforcement	Mineral		
Additive	UV Stabilizer		
Features	Copolymer		
	Good Processability		
	Good UV Resistance		
	High Flow		
	High Stiffness		
	Medium Impact Resistance		
Uses	Automotive Applications		
	Automotive Interior Parts		
Appearance	Colors Available		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.00	g/cm³	ISO 1183/A
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	28	g/10 min	ISO 1133
Molding Shrinkage	0.90 to 1.1	%	Internal Method
Mechanical	Nominal Value	Unit	Test Method
Flexural Modulus ¹ (23°C)	1800	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	4.0	kJ/m²	ISO 180/1A
NOTE			
1.	2.0 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

