

REVOLVE® N-270

Polyethylene
Matrix Polymers

Message:
Revolve N-270 is a fully formulated rotomoulding grade designed for general purpose applications and small tanks. The resin has medium stiffness, good impact strength, ductility and mouldability.

General Information			
Features	Ductile		
	General Purpose		
	Good Impact Resistance		
	Good Moldability		
	Good Stiffness		
Uses	General Purpose		
	Tanks		
Appearance	Black		
	Colors Available		
	Natural Color		
Forms	Granules		
	Pellets		
	Powder		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.936	g/cm ³	ISO 1183
Melt Mass-Flow Rate (MFR)	4.0	g/10 min	ISO 1133
Environmental Stress-Cracking Resistance			ASTM D1693
10% Igepal	50.0	hr	
100% Igepal	> 1000	hr	
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	16.5	MPa	ISO 527-2/50
Flexural Modulus ¹	657	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
ARM Impact (3.00 mm)	90.6	J	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	43.0	°C	ISO 75-2/A
NOTE			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

