

# Huaфон JF-S-DR9020

Polyurethane  
Huaфон Group Co., Ltd.

Message:  
Special Type for Surface Layer  
Characteristics  
Special resin for Yangbuck Leather, solvent resistance, uniform foaming, delicate texture, good fastness.  
Applications  
Yangbuck foaming

General Information		
Features	Foamable	
	Solvent Resistant	
Uses	Foam	
Additional Information	Nominal Value	Unit
Solvents	DMF/MEK/TOL	
Uncured Properties	Nominal Value	Unit
Solids Content	19 to 21	%
Viscosity (25°C)	1.0 to 3.0	Pa·s
Cured Properties	Nominal Value	Unit
Tensile Modulus (100% Secant)	1.00 to 2.00	MPa

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT