# LNP™ STAT-KON™ RX05489 compound

### Polyamide 66

#### **SABIC Innovative Plastics**

#### Message:

LNP STAT-KON RX05489 is a compound based on Nylon 66 resin containing PTFE, Carbon Fiber. Added features of this material include: Electrically Conductive, Internally Lubricated. Also known as: LNP\* STAT-KON\* Compound RCFL-4536 Product reorder name: RX05489

General Information		
Filler / Reinforcement	Carbon fiber reinforced material	
Additive	PTFE lubricant	
Features	Conductivity	
	Lubrication	

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.43	g/cm³	ASTM D792
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus <sup>1</sup>	15300	MPa	ASTM D638
Tensile Strength (Break)	172	MPa	ASTM D638
Tensile Elongation (Break)	2.6	%	ASTM D638
Flexural Modulus	14400	MPa	ASTM D790
Flexural Strength	296	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	130	J/m	ASTM D256
Unnotched Izod Impact (23°C)	960	J/m	ASTM D4812
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed, 3.20 mm)	247	°C	ASTM D648
Electrical	Nominal Value	Unit	Test Method
Surface Resistivity	1.0 - 6.0	ohms	ASTM D257
NOTE			
1.	50 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

